

# Thinkpad on Linux

## Remap keys

I am using this to remap keys for faster navigation. When you pres [Fn] key, the cursor arrows are mapped as follows:

```
[ PGUP ]  
[HOME] [PGDOWN] [END]
```

[~/Xmodmap](#)

```
keycode 171 = End  
keycode 172 = Next  
keycode 173 = Home  
keycode 174 = Prior
```

[~/xprofile](#)

```
#tested on ThinkPad x201  
xmodmap -e "keycode 174 = Prior"  
xmodmap -e "keycode 172 = Next"  
xmodmap -e "keycode 173 = Home"  
xmodmap -e "keycode 171 = End"
```

## ThinkFan

[/etc/modprobe.d/options.conf](#)

```
options thinkpad_acpi fan_control=1 fan="level disengaged" beep=6
```

[/etc/thinkfan.conf](#)

```
(0, 0, 40)  
(5, 32, 60)  
(6, 59, 70)  
(7, 69, 95)  
("level disengaged", 90, 32767)
```

```
echo thinkpad_acpi > /etc/modules  
modprobe thinkpad_acpi
```

```
systemctl enable thinkfan
systemctl start thinkfan
```

## Modem

- Pro Vodafone stáhnout [tyto oladače](#) a rozbalit do adresáře `/lib/firmware/gobi`
- Nainstalovat balicky `apt-get install gobi-loader modemmanager`
- Nepridavat `05c6:9205` (z `lsusb`) do `/usr/lib/udev/rules.d/60-gobi.rules` !!! je to USB ID po nahrani FW, pred nahranim to ma `05c6:9204` a to uz tam je. Pokud se tam nahraje i to prvni, tak to dokola loaduje fw a nenabehne to.
- Restartovat pocitac
- Po pripojeni skrz networkmanager lze nainstalovat a pouzit program `modem-manager-gui` k posilani a prijmani SMS, USSD kodu a sledovani detailu pripojeni

## odkazy a drivery pro ostatni operatory

- [http://www.thinkwiki.org/wiki/Qualcomm\\_Gobi\\_2000](http://www.thinkwiki.org/wiki/Qualcomm_Gobi_2000)
- <http://support.lenovo.com/us/en/downloads/ds001302>

## Thinklight

Dame vsem prisup k LEDkam:

[/etc/udev/rules.d/10-thinklight.rules](#)

```
SUBSYSTEM=="leds", ACTION=="add", RUN+="/bin/chmod -R o=u,g=u /sys%p"
SUBSYSTEM=="leds", ACTION=="change", ENV{TRIGGER}!="none",
RUN+="/bin/chmod -R o=u,g=u /sys%p"
```

Rebootneme nebo reloadneme `udevadm control --reload-rules; udevadm trigger --verbose`

Potom vytvorime tenhle skript s pravama pro spusteni:

[/usr/local/bin/thinklight](#)

```
#!/bin/sh
led='/sys/class/leds/tpacpi::thinklight/brightness';
state=$(cat "$led");
[ "$state" == 0 ] && new=255 || new=0;
echo "${1:-$new}" > "$led";
```

Muzem pouzivat tyhle prikazy

- `thinklight` - vypne/zapne svetylko (idealni jako ikonka na listu)

- thniklight 0 - vypne
- thniklight 255 - zapne

From:

<https://wiki.spoje.net/> - **SPOJE.NET**

Permanent link:

<https://wiki.spoje.net/doku.php/howto/desktop/thinkpad?rev=1508242382>

Last update: **2017/10/17 14:13**

