

ispconfig - poznamky k implementaci

Multiserver instalace

Vlastni login k master databazi

V multiserver rezimu muze byt nekdy uzitecne vnuteni vlastniho uzivatele bez prav k celému db serveru, kde master databaze bezi. V takovem pripade je potreba upraveny login zmeni v techto souborech:

```
/usr/local/ispconfig/interface/lib/config.inc.php  
/usr/local/ispconfig/server/lib/config.inc.php
```

Druha varianta je vytvorit v obou adresarich config.inc.local.php kam presuneme nase nastaveni pripojeni k master databazi

PHP

Vzhledem k moznosti vice verzi PHP je dobre definovat vychazi hodnoty nekde bokem a pak vlozit symlinky do /etc/php/7.0*/conf.d/05-php-default.ini napr.

```
memory_limit = 48M  
upload_max_filesize = 64M  
max_file_uploads = 30  
post_max_size = 64M  
sendmail_path = "/usr/sbin/sendmail-php -t -i"  
date.timezone = "Europe/Prague"
```

From:

<https://wiki.spoje.net/> - **SPOJE.NET**

Permanent link:

<https://wiki.spoje.net/doku.php/howto/hosting/ispconfig/poznamky?rev=1515592331>

Last update: **2018/01/10 14:52**

