

# Redmine

## Aktualizace

- Pokud migrujeme z verze 1.3.x do 2.x, nainstalujeme nejdriv

```
apt-get install ruby-dev
gem install bundler
```

- Zazalohujeme databazi
- Zazalohujeme adresar **public, config**
- Ostatni adresare a soubory krome adresare **files** smazeme a nakopirujeme novou verzi
- Ze stareho adresare config prekopirujeme soubory **configuration.yml** a **database.yml**

*Pokud pouzivame ruby 1.9 a vyssi, zmenime v soubory database.yml radek adapter: mysql ⇒ adapter: mysql2*

*Do souboru configuration.yml (pokud tam jeste neni), pridame secret\_token: 'abcd' kde abcd bude nahodny retezec*

- Prepneme se do root adresare redmine a spustime instalaci. Pokud pouzivame pluginy, je dobre vsechny zavislosti na dalsim gems vyjmenovat do souboru **Gemfile**

```
bundle install --without development test
```

- Pokud aktualizujeme z verze 2.5.x na novejsi, pouzijeme prikaz bundle update
- Nyni provedeme migraci databaze

```
bundle exec rake generate_secret_token
bundle exec rake db:migrate RAILS_ENV=production
```

- Pokud mame nejake plguiny

```
bundle exec rake redmine:plugins:migrate RAILS_ENV=production
```

- A na zaver vycistime cache

```
bundle exec rake tmp:cache:clear tmp:sessions:clear
```

- Nyni provedeme restart Apache

## Poznamky pri instalaci pluginu

Pokud provedeme nejakou zmenu ve strukture databaze, je nutne vzdy potom zavolat bundle exec rake db:migrate RAILS\_ENV=production v root adresari redmine a potom restartovat Apache

Pokud provedeme instalaci noveho pluginu (umistujeme do adresare **plugins**), je nutne zavolat rake redmine:plugins:migrate RAILS\_ENV=production a potom restartovat Apache  
Pokud chceme plugin odinstalovat, je potreba zavolat rake redmine:plugins:migrate

NAME=plugin\_name VERSION=0 RAILS\_ENV=production, potom smazat plugin z adresare **plugins** a restartovat Apache

## Napojeni na nextcloud

```
CREATE VIEW nextcloud_user AS
SELECT users.login, users.hasheds_password, users.salt,
email_addresses.address
FROM users
INNER JOIN email_addresses ON (users.id=email_addresses.user_id)
WHERE users.status=1 AND users.type="User";
```

## Instalace konkretni verze bundle

```
gem install bundler -v 1.16.1
bundler -v
```

```
Bundler version 1.16.1
```

```
gem uninstall bundler
```

```
Select gem to uninstall:
1. bundler-1.17.1
2. bundler-2.1.4
3. All versions
```

## Problemy

### send\_notification

Pokud po aktualizaci redmine zaznamename pri vkladani poznamek k ticketu nasledujici chybu

```
translation missing: en.field_send_notification changed from 0 to ---
!ruby/object:Mail::Message body: !ruby/object:Mail::Body boundary: --
==_mimepart_52a0ad837f377_63933fb8c3f4a54081298 preamble: ....
```

potom je potreba odstranit v tabulce **issue** sloupec **send\_notification** a nasledne potom zavolat prikaz `bundle exec rake db:migrate RAILS_ENV=production` a restartovat apache.

Pokud uz se nam prihodilo, ze jsou nektere poznamky k ticketu o tyto hlasku prodlouzeny, najdeme je a smazeme z tabulky **journal\_details**

## Chyba 500 pri ukladani ukolu nebo nahodne pri nacistani ticketu s prilohama

```
PassengerUploadBufferDir /cesta/redmine/passenger/
```

a zkontrolovat ze v adresari redmine tento existuje a ma do nej apache pravo zapisu

Od verze 5 se to jmenuje - **PassengerDataBufferDir**

### Upgrade ruby na 2.3

- po upgradu ruby je potreba znova nainstalovat bundler **gem install bundler** pripadne doinstalovat dalsi zavilosti ktere se zjisti pri naslednem zusteni bundle install

### redmine\_agile

We had the same issue and after some investigations, we found that the problem was generated by the redmine\_agile plugin.

```
/assets/stylesheets/redmine_agile.css
```

```
html {  
- overflow-y: inherit !important;  
+ /* overflow-y: inherit !important; */  
}
```

From:

<https://wiki.spoje.net/> - **SPOJE.NET**

Permanent link:

<https://wiki.spoje.net/doku.php/howto/hosting/redmine?rev=1596462224>

Last update: **2020/08/03 15:43**

