

# nftables

## Traffic Shaping with nftables and tc

This patch is already merged upstream:

[nft-classid.patch](#)

```
parser: allow classid as set key

From: Arturo Borrero Gonzalez <arturo@xxxxxxxxxxxxxx>

Allow TC classid as set key.

Signed-off-by: Arturo Borrero Gonzalez <arturo@xxxxxxxxxxxxxx>
---
 src/parser_bison.y |    1 +
 1 file changed, 1 insertion(+)

diff --git a/src/parser_bison.y b/src/parser_bison.y
index 7016f5b..2918875 100644
--- a/src/parser_bison.y
+++ b/src/parser_bison.y
@@ -1545,6 +1545,7 @@ type_identifier      : STRING      { $$ = $1; }
          | MARK        { $$ = xstrdup("mark"); }
          | DSCP        { $$ = xstrdup("dscp"); }
          | ECN         { $$ = xstrdup("ecn"); }
+         | CLASSID    { $$ = xstrdup("classid"); }
;

hook_spec      : TYPE      STRING      HOOK      STRING
dev_spec      : PRIORITY   prio_spec
```

```
nft add map filter deucalion { type ipv4_addr : classid\; }
```


[deucalion.nft](#)

```
map deucalion {
    type ipv4_addr : classid;
    elements = { 1.1.1.2 : 2:2222, 1.1.1.3 : 3:3333 }
}

chain input {
    type filter hook input priority 0; policy accept;
    meta priority set ip daddr map @deucalion;
```

}

From:  
<https://wiki.spoje.net/> - **SPOJE.NET**



Permanent link:  
<https://wiki.spoje.net/doku.php/howto/network/nftables?rev=1543438753>

Last update: **2018/11/28 21:59**